

# PLUS SN 5W30



## Sintetiki motor ýagy

TM-Ajaryp yokary ondürijilikli we az ýangyg sarp edilmegini upjun edyan dort pasyl sintetiki hereketlendiriji yagydyr. Ýolag^y awtoulaglarynda we gonuden-goni benzin we turbodizel hereketlendirijileri ya-da katalitik owrujileri bolan yenil sowda ulaglarynda ulanmak maslahat berilyar. Yssy howa şertlerinde in täze hereketlendirijilerin az ýag sarp etmegi standartlaryna layyk gelmek u^iň yorite sintetiki esasda ondurilendir. Hereketlendirijinin optimal işlemegi u^iň daşky gur^aw temperatura diapazony: -30 °C / +40 °C. Gowy şemalladylyan yerde berk yapylanda we gün şdhlesinden goralsa, kepillendirilen yaramlylyk mohleti: bndurilen gununden5yyl.

## Synthetic Engine Oil

GB-Excellent high performance and low fuel consumption multigrade synthetic engine oil. Recommended for use direct injected (GDI) or/ and equipped with catalytic converter type gasoline or diesel new generation passenger cars and light commercial vehicles. Specially formulated synthetically to meet latest engine standarts lowest oil loss at hot climate conditions. Recommended ambient temperature range for optimum engine performance: -30 °C/+40 °C. Shelf life is up to 5 years if, package tightly closed and protection from sunlight in well ventilated area storage.

## Синтетическое моторное масло

RU-Bcece3OHHe cHTeTumecKoe MoropHoe Maeno c oTnuMHbIMM bbicoki/imii/i aKcnyiaTaqnoHHbIMy xapaKTepycTUKaMM ii hmskm pacxofOM TonnuiBa. PeKOMeHflyeTcfl flnH ucnob3OBaHnH c HenocefICTBeHHbIM BnpbickOM (GDI) n/nnn obopyiOBaHHbix KaTanuTWMecKUM HeiiTpanusaTopoM 6eH3MHOBBix uinn flusenbHbix ABuraTenei nerKOBbix aBTOMo6nnew HOBoro nokoneHnn ii nerki/ix KOMMepqecKMx aBTOMo6wneu. CneqnanbHo paspaoTano Ha CMHTeTMMecKOH oCHOBe, mto6H cooTBECTBOBaTb hoBeiiinUM CTaHflapTAM flnn flBi/iraTenei/i c Mi/iH/iManbHbIM/i noTepMH Macna b >KapKHx KHHMaTbqecKMx ycnoBwnx. PeKOMeHflyeMbiM flwanasoH TeMnepaiyibi OKpyKaiolneii epeflbi ana onTi/iManbHoii pabo™ ABkiraTenn: -30 °C / +40 °C. CpoK toaocTm flo 5 neT c aaTbi npon3BOICTBa npi nnoTno saKpbIToii ynaKOBKe m 3annTe ot conneMHbix nyneki b xopoiuo npoBeTpi/iBaEMOM noMemeHWM.



Fiziki we himiki ayratynyklary / Physical and Chemical Properties OM3MqecKHe u xumHqecKHe ceoiCTBa	Usui/ Method /Melon	Aklar / Limits / OrpaHmeim
Klassifikasiya / Classification / Классификация	-	SAE 5W30
Reňk/Color/Цвет	-	Açyk Goňur / Light Brown Светло-коричневый
Dykyzlygy/Density/ Интенсивность, 15 °C, gr / cm <sup>3</sup>	TDS 25371 / ASTM D 4052	0,85
Kinematiki Şepbeşikligi/Kinematic Viscosity / Кинематическая вязкость, 100 °C, cSt	TDS 1003/ ASIM D 445	9,3-12,5
Şepbeşiklik Indeksi/Viscosity Index/Индекс вязкости	TDS 25371 / ASTM D 2270	>160
Sowama temperaturasy / Pour Point / Температура застывания, °C	TDS 966 / ASTM D 97	< -36
Agk tiglde kesgitlenyan ot alma temperaturasy/Flash Point Tomka BO3ropaHnn, °C	TDS4333/ASTM D92	>210



Talaplaryna Layyk Gelyar/Meets Requirements/CoOTBeTCTByeT Tpe6oBaHuiAM :  
API SN/CF, ILSAC GF-5,  
Hem maslahat berilyar/Also recommended/ Taroxe peKOMeH^yeTCfi:  
GM Dexos®1 Gen2, BMW, Honda, Hyundai, Kia, Lexus, MB, Mitsubishi, Nissan, Subaru, Toyota



TŞ 02626956-02-2022 [f](#) [y](#) [v](#) /siryag • www.siryag.com

Öndürilen yeri / Production Place / Meno npoiBBOiciBa

Mjneral we sintetik ýagy ondiiryan zawod: Lebap welayatymyn Danew etrabynyn Ajgabat gene^liginin Abadan obasynyn Nebitg kogsinin 11-nji salgysy, Tel.: (+993) 4466 1054

"Asudaakym"hojalykjemgyeti.AjgabatŞaheri, Berkararlyketraby, TagmammetSuhangulyyewk6gesi, 43jyayT. +9936141 3272

